

TOTO Wall-mounted automatic one-piece urinal

USWN900BS(Sanitizing Technology)



USWN900BS

FEATURES

- Integral design of inductor and urinal building more stylish public space
- Carrying sterilized water can inhibit the adhesion of dirt in urinal trap.
- Automatic flushing for 2 hours can inhibit the adhesion of urinary stones in the horizontal drainage pipe of urinal.
- Low height design, meet the needs of more people
- With CeFiONtect and smooth surface exceeding nanometerclass designed for providing, no gap to contain adhered stain and ensuring easier cleaning, without need of excessive water and cleaning agent
- Inductive flush without contact during the whole process, secure and sanitary for use
- Interval flush with sanitizing flush keeps easy maintenance for drainage pipe.
- The control part is on the top of the product, easy for maintenance.

完成墙面 ★开关接收盒 (客户自备) 给水位置 挂钩位置 23 545 920) 110 2 de50 PVC (350) 225) 100 (340) 完成地面 ※1仅限USWN900BE交流电用 ※2 排水管的安装方法请参考产品 随附的安装说明书 ()建议安装尺寸

*TOTO公司保留对其产品规格和尺寸更改的权利。届时,恕不另行通知。

*TOTO(CHINA) CO., LTD. All rights reserve.

TOTO (CHINA) CO., LTD. www.toto.com.cn

Wall-mounted automatic one-piec SPECIFICS

Size: 380*420*920mm Water supply: 0.07MPa(Dynamic Pressure)~ 0.75MPa(Static Pressure) Water flush:0.5L Water efficiency grade: Grade 1 Power: 220V(50Hz) Water inlet model: Rear water spout Sensing distance: 650mm away from the front of inductive window Installment: Wall-mount

USWN900B/USWN900BE/USWN900BS